




HSM2HOSTx PowerG Host Transceiver Module

- Supports up to 128 wireless zones and 32 wireless keys – varies per panel
- Supports DSC PowerG devices
- Compatible with PGx920 PowerG Repeater for range extension
- All wireless detectors are fully supervised for communication integrity


Available in NA, LATAM, Europe, Africa and APAC



HSM2300 Power Supply Module

- Fully supervised for AC failure, low battery and AUX failure
- Provides up to 1 Amp @ 12 VDC


Available in NA, LATAM, Europe, Africa and APAC



HSM2204 High Current Output Module

- Fully supervised for AC failure, low battery and AUX failure
- 4 programmable high current voltage outputs: rated at 1 Amp @ 12 VDC
- Output #1 can be used as a supervised bell output
- Provides up to 1 Amp @ 12 VDC


Available in NA, LATAM, Europe, Africa and APAC



HSM2208 Output Module

- Provides 8 low current (50 mA) programmable outputs

Available in NA, LATAM, Europe, Africa and APAC



HSM2108 Hard wired zone expander

- Adds 8 hardwired zones
- AUX power up to 125 mA (PTC protected)


Available in NA, LATAM, Europe, Africa and APAC



HSM2955(R) Two-Way Audio Module

- Up to 4 two-way audio stations supported
- Optional recording of up to 15 minutes of pre-alarm activity
- Supports both 2-way audio VOX and push-to-talk verification
- Silent/Listen-in functionality on hold-up alarms (activates only when an alarm occurs)
- Two-way audio over PSTN or Cellular
- Supports PC5961E small and PC5964E large audio stations

Available in NA and EMEA



PCL-422 Communicator Remote Mounting Module

- Allows extension of the PC-LINK connection by 50 ft (15 m) so communicator can be mounted in separate enclosure from panel
- Distance can be extended up to 1000 ft (300 m) if additional power supply is used
- Compatible with 3G2080(E), TL2803G(E) and TL280(E) alarm communicators

Available in NA, LATAM, Europe, Africa and APAC

3G8080(I) / CD8080(I) PowerSeries Neo HSPA / CDMA Cellular Alarm Communicator

- 4 integrated communicator models: 3G8080; 3G8080I*; CD8080**; CD8080I*/**
- 2 integrated cellular technologies: HSPA (3G); CDMA**
- Antenna Extension Kits available: GS-15ANTQ, GS-25ANTQ, GS-50ANTQ
- Signal strength and trouble display
- PC-Link connection
- Compatible with HS2016/ HS2032/ HS2064/ HS2128 control panels
- Compatible with Sur-Gard System I -IP/II/III/IV/5 monitoring station receivers
- Compatible with alarm.com

Available in NA, LATAM, Europe, Africa and APAC

* Required for supporting image sensors ** Only available in US

3G2080(R)E HSPA Cellular Alarm Communicator

- Back up and primary Cellular alarm communication
- Panel remote uploading/downloading support via Cellular
- Supervision heartbeats via Cellular
- 128-bit AES encryption via Cellular
- Full event reporting
- SIA and Contact ID protocol
- Remote activation and programming through C24 Communications (North America Only)
- Signal strength and trouble display
- Visual verification over Cellular
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- Command and Control via SMS
- R model includes RS232 serial integration option
- Provides expanded user support with PowerSeries Neo HS2064 and HS2128 panels V1.2 and higher

Available in NA, LATAM, Europe, Africa and APAC

TL2803G(R)E Internet and HSPA Dual-path Alarm Communicator

- Fully redundant Internet and Cellular dual-path alarm communication
- Integrated call routing
- Panel remote uploading/downloading support via Cellular and Internet
- Supervision heartbeats via Cellular and Internet
- 128-bit AES encryption via Cellular and Internet
- Full event reporting
- SIA and Contact ID protocol
- Remote activating and programming through C24 Communications (North America Only)
- Active Cellular account is required to use IP function
- Signal strength and trouble display
- Visual verification over Cellular or Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- Command and Control via SMS
- R model includes RS232 serial integration option supports up to 4 integration paths over Ethernet
- Provides expanded user support and up to 4 ethernet integrations with PowerSeries Neo panels HS2064 and HS2128 V1.2 and higher

Available in NA, LATAM, Europe, Africa and APAC

T280(R)E Internet Alarm Communicator

- Panel remote uploading/downloading via Internet
- Programmable using DLS 5 or keypad
- Supervision heartbeat via Internet
- 128 Bit AES Encryption
- Full event reporting
- SIA and Contact ID protocol
- Visual verification over Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- R model includes RS232 serial integration option
- Provides expanded user support (HS2064/ HS2128) and up to 4 ethernet integrations with PowerSeries Neo panels V1.2 and higher
- Refer to www.dsc.com for complete list of integration options

Available in NA, LATAM, Europe, Africa and APAC

Some products are not available in all countries. Please contact your local distributor or refer to www.dsc.com for the most current approval listings.

