

From Tyco Security Products



Wireless PowerG Indoor Siren **PG4901**

(Applicable to Brazil, Peru, Uruguay, Asia Pacific excluding China)

Features That Make a Difference:

- PowerG* robust industry leading commercial grade wireless technology
- Visible link quality indicator on device
- 110db Siren with Strobe Light
- Siren sounds for Fire, Carbon Monoxide, Burglary and Flood Events
- Long-life lithium batteries (sold separately)
- Compatible with PowerSeries
 Neo and iotega systems

The power of PowerG:*

The power behind our latest products lies in various innovative technologies, including the revolutionary PowerG, which, bundled together, provide a robust and feature-rich platform designed to reduce operational costs for dealers and provide ultimate reliability for end users.

- Multichannel, Frequency Hopping Spread Spectrum technology - to overcome frequency blocking and interference
- Adaptive Transmission Power for battery life preservation
- High transmission ranges for reliable communication within up to 2km/2187 yards line-of-sight
- TDMA synchronized communication technology - to prevent message collisions
- 128 bit AES encryption high level protection against analysis tools and digital attacks







Wireless PowerG PG4901 Indoor Siren

The PG4901 Wireless PowerG Indoor Siren is a fully supervised, cost effective siren that provides differentiated audible and visual alerts in the case of fire, carbon monoxide, burglary and flood events. In addition to providing a loud audible alert, the PG4901 also contains a built-in high-power white strobe light providing a visual alert of the event.

With its sleek and modern design, the PG4901 will fit most internal spaces.

Easy to Install | Signal Quality Indication

Since the PG4901 is wireless, it can conveniently be installed in numerous locations inside the home. With fewer holes to drill and reduced installation time, an installer can quickly move on to another installation.

The PG4901 Wireless PowerG Indoor Siren is equipped with a visible signal quality LED indicator that lets the installer choose the optimal location for installation, eliminating the effort of going back and forth to the keypad. All siren configuration settings are handled on the keypad with no need to reopen the device once installed.



Specifications:

Dimensions:	161 x 161 x 50mm
	(6-7/16 x 6-7/16 x 1-3/4in)
Battery Life:	8 years (typical use)
Battery Type:3.6V, L	i-Thionyl Chloride 0-102710
Weight (including battery):	470gr (16.5oz)
Operating Temperature:	10°C to 55°C (14°F - 131°F)

Approvals:

FCC/IC, UL/ULC, CE, CCC, SRRC, C-Tick, ANATEL, WPC, IDA

Please refer to www.dsc.com for the most current approval listings. Product varies depending on country.

Compatibility:

PowerSeries Neo and iotega systems