

## Wireless PowerG Panic Key **PG4938**

(Applicable to Brazil, Peru, Uruguay,  
Asia Pacific excluding China)



### Features That Make a Difference:

- **PowerG\*** robust industry leading commercial grade wireless technology
- Visual acknowledgement of requested action
- Full two-second delay on panic button
- Long-life lithium batteries included
- Compatible with PowerSeries Neo systems

#### **The power of PowerG\*:**

The power behind our latest products lies in various innovative technologies, including the revolutionary PowerG, which, bundled together, provide a robust and feature-rich platform designed to reduce operational costs for dealers and provide ultimate reliability for end users.

- Multichannel, Frequency Hopping Spread Spectrum technology - to overcome frequency blocking and interference
- Adaptive Transmission Power - for battery life preservation
- High transmission ranges - for reliable communication within up to 2km/2187 yards line-of-sight
- TDMA synchronized communication technology - to prevent message collisions
- 128 bit AES encryption - high level protection against analysis tools and digital attacks

PowerSeries  
**neo**  
compatible

**iotegea**<sup>®</sup>  
compatible

### Wireless PowerG PG4938 Panic Key

The PG4938 Wireless PowerG Panic Key is a portable personal protection device which allows users to send an emergency notification to the security system, via one large, easy-to-use button, thus alerting authorities. This attractive, compact and water-resistant panic key can be worn around the neck or permanently mounted/clipped to a belt with the multifunction clip.

#### **Visual Indication**

When the button of the PG4938 is pressed, the visual LED indicator confirms the command has been successfully carried out by the security system. The confirmation that the message has been executed by the security system offers 'peace of mind' to users.

### False Alarm Reduction

The PG4938 is equipped with a full two-second activation delay to help reduce false alarms, thus minimizing costly false dispatches caused by accidental activations.

#### **Easy To Use**

With only a single, large and clearly defined panic button, the PG4938 allows for trouble-free activation in stressful emergency situations. Portable and simple to use, it allows users to call for support from anywhere within the premises.



From Tyco Security Products

### **Specifications:**

Dimensions:..... 53 x 33 x 11mm (2.1 x 1.3 x 0.4in)

Battery Life: .....5 years (Typical usage)

Battery Type: .....3V, CR2032

Weight: ..... 15g (0.5oz)

Operating Temperature: .. -10°C to 55°C (14°F to 131°F)

### **Approvals:**

FCC/IC, UL/ULC, CE, C-Tick, ANATEL, WPC, IDA

Please refer to [www.dsc.com](http://www.dsc.com) for the most current approval listings.

Product varies depending on country.

### **Compatibility:**

PowerSeries Neo and iotega systems